

Port Atlantic House Noorderlaan 147b9 2030 Antwerp - Belgium



www.liquisol.com 230426

Dit document is een voorbeeld van de garantie die enkel de Authorised Liquisol Applicator kan geven op een werk uitgevoerd met de 4EVERblue of 4EVERdark coating op lichtstraten en licht koepels.

This document is an example of the guarantee that only the Authorised Liquisol Applicator can give on a job performed with the 4EVERblue or 4EVERdark coating on skylights and light domes.

Ce document est un exemple de la garantie que seul l'Authorised Liguisol Applicator peut donner sur un travail réalisé avec le revêtement 4EVERblue ou 4EVERdark sur les lanterneaux et coupoles.

Dieses Dokument ist ein Beispiel für die Garantie, die nur der Authorised Liquisol Applicator für eine mit der Beschichtung 4EVERblue oder 4EVERdark auf Oberlichtern und Lichtkuppeln ausgeführte Arbeit geben kann.

Este documento é um exemplo da garantia que só o Authorised Liquisol Applicator pode dar sobre um trabalho efectuado com o revestimento 4EVERblue ou 4EVERdark em clarabóias e cúpulas luminosas.

Este documento es un ejemplo de la garantía que sólo el Authorised Liguisol Applicator puede dar sobre un trabajo realizado con el recubrimiento 4EVERblue o 4EVERdark en claraboyas y cúpulas de luz.

Questo documento è un esempio della garanzia che solo l'Authorised Liguisol Applicator può fornire su un lavoro eseguito con il rivestimento 4EVERblue o 4EVERdark su lucernari e cupole luminose.



European Limited Warranty for

4EVERblue and 4EVERdark

Liquisol bvba warrants to the first customer of the 4EVERblue and/or 4EVERdark ("the Product") identified in the fully completed and signed Record of Installation that if the Product has been correctly applied on a surface with a minimum slope of 15% by an Authorised Liquisol Applicator but peels, cracks, crazes or fails to adhere by reason of defective Product during the applicable warranty period of 5 years, it will supply new product free of charge. Additionally, the colour stability of the product are covered by this warranty.

This Warranty is only valid where:

- The Product has been applied by an Authorised Liquisol Applicator; and
- The Product has been applied in accordance with the instructions as outlined in the 2017 Liquisol application Manual; and
- The customer notifies the authorised Liquisol Applicator in writing within one month of the defect appearing; if it is not practical for the customer to notify the Authorised Liquisol Applicator, written notice should be given to Liquisol byba directly; and
- Within 30 days after the application, the Paints and varnishes Cross-cut test has been performed with an Elcometer 1540 and the result is classification 1-3.

Installation (in the form attached) was fully completed and signed on or around the time of completion of the installation and sent to Liquisol bvba. Any notice of defect must be mentioned.

Record of Installation

Authorized Liquisol Applicator					
Company: Liquisol					
VAT: be0648867048	Applicator: tom huysmans				
City: Antwerpen	Address:Noorderlaan 147b9				
Postal code: 2030	Country:Belgium				
Phone: 00 32 474 625 693	Mail: verf@liquisol.com				
Customer					
Company: DHL Aviation NV					
Responsible:Krist					
City: Diegem	Address:Woluwelaan 145				
Postal code: 1831	Country:belgium				
Phone: +32 2 719		lhl.com			

Liquisol bvba Noorderlaan 147b9 2030 Antwerp Belgium 003232560172 ALA@liquisol.com

Туре	Surface	Area	Batch	# 5-liter bags	Date	СНС	CHC date
4EVERBLUE	POLYCARBONAT	30m²	4BAID1	1	21-11-2019	5	21-11-2019

This Warranty is not valid where:

- The coating was not installed by an authorised Liquisol Applicator; or
- The Record of Installation was not fully completed and signed on or around the time of completion of the installation and sent to Liquisol byba; or
- The product is removed by the customer before Liquisol byba and the Authorised Liquisol Applicator have inspected a reported defect; or
- The failure is due to a surface or a framing system failure; or
- The product has been modified or repaired by a person not authorised by Liquisol byba; or
- The product has been subjected to abnormal use, misuse or neglect; or
- The product has not been installed in line with the installation guidelines recommended in the 2017 Liquisol Application Manual; or
- The product defect is due to a lack of, or improper maintenance and cleaning not in conjunction with Liquisol's recommendations; or
- The product is over 2 years old since the date of purchase before it was installed; or
- Prior to the installation, the product was not stored in its original packaging nor under the environmental conditions as recommended by Liquisol bvba.
- Within 30 days after the application, the Paints and varnishes Cross-cut test has been performed with an Elcometer 1540 and the result is classification 1-3. Or no test has been performed.

Where Liquisol 4EVERblue and 4EVERdark is applied by a non-Authorised Liquisol Applicator, Liquisol byba's warranty applies for a maximum of 1 year across the product.

In the event of a successful claim resulting in new coating being applied, the warranty period for the replacement coating will only be if the remaining period from the previous application.

This Warranty is given in place of and excludes all other warranties and conditions, whether express or implied by statute or common law. Nothing in this Warranty shall be deemed to exclude or restrict Liquisol bvba's liability for death or personal injury resulting from Liquisol bvba's negligence. Liquisol bvba shall not be liable for any consequential or indirect loss or damage whatsoever whether arising from the supply of the Product, its use, from any defect or failure in its performance or in any other way. Liquisol bvba's liability under this Warranty shall never exceed the cost of replacing the Product.

This Warranty may only be assigned by the customer during the Warranty Period and only then with Liquisol byba's and the Authorised Liquisol Applicator's prior written consent.

Image of the job:



Image of the cross hatch test result:




ISO 2409:2007(E)

Classification	Description	Appearance of surface of cross-cut area from which flaking has occurred		
		(Example for six parallel cuts)		
0	The edges of the cuts are completely smooth; none of the squares of the lattice is detached.	_		
1	Detachment of small flakes of the coating at the intersections of the cuts. A cross-cut area not greater than 5 % is affected.			
2	The coating has flaked along the edges and/or at the intersections of the cuts. A cross-cut area greater than 5 %, but not greater than 15 %, is affected.			
3	The coating has flaked along the edges of the cuts partly or wholly in large ribbons, and/or it has flaked partly or wholly on different parts of the squares. A cross-cut area greater than 15 %, but not greater than 35 %, is affected.			
4	The coating has flaked along the edges of the cuts in large ribbons and/or some squares have detached partly or wholly. A cross-cut area greater than 35 %, but not greater than 65 %, is affected.			
5	Any degree of flaking that cannot even be classified by classification 4.			

Table 1 — Classification of test results

Liquisol bvba Noorderlaan 147b9 2030 Antwerp Belgium 003232560172 <u>ALA@liquisol.com</u> Scan the QR-code to check if this warranty is an official document of Liquisol.



Approved by Liquisol byba on 03/12/19